

# CERTIFICATE

## of constancy of performance

### 1922 - CPR - 0751

In compliance with Regulation (EU) 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

**Exterior Grade Compact Laminate with flame retardant (thickness - more than 2.0 mm), Interior Grade Compact Laminate with flame retardant (thickness - more than 2.0 mm), Composite high pressure laminate (HPL) with flame retardant (thickness - less than 2.0 mm)**

(List of tested characteristics described in Annex I, that is an integral part of this certificate)

placed on the market under the name or trade mark of

**M/s GREENLAM INDUSTRIES LIMITED**

**2ND FLOOR, WORLD MARK 1, WEST WING, IGI AIRPORT HOSPITALITY  
NEW DELHI, NORTH WEST DELHI, DELHI, 110037, INDIA**

and produced in the manufacturing plant

**M/S GREENLAM INDUSTRIES LIMITED**

**VILL PATERH BHONKU, PO- PANJEHRA, TEHSIL-NALAGARH,  
DISTRICT-SOLAN, HIMACHAL PRADESH, PIN CODE-174101, INDIA**

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

**EN 438-7:2005**

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

This certificate was first issued on 09.09.2016 and will remain valid until 09.09.2024 as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body. The certificate is supported through annual surveillance audit and is reissued after each surveillance audit. The validity of the certificate may be confirmed in the CE register at the web address [www.dedal-bg.net](http://www.dedal-bg.net).



Manager: *Anna Vasileva*

 dipl. eng. Anna Vasileva

Issued:  
Burgas, 09 August 2023

Ref. No. 03-00

## ANNEX I TO CERTIFICATE OF CONSTANCY OF PERFORMANCE 1922 - CPR - 0751/09.08.2023

List of controlled characteristics:

Characteristics, dimension	Clause	Method	Results			
			COMPACT BRANDS			HPL BRANDS
			Greenlam Exterior Clads™, EDF/EDS New Mika Fx EDF	Greenlam Safeguard Plus (CGF)	Greenlam Labguardian Chemical Resistance Laminate	GREENLAM, NEWMIKA, GREENTOUCH, NEW POINT EIGHT, SPLENDOR, UNICORE, HD-GLOSS & POSTFORMING LAMINATE
Thickness			6.0 mm	12.0 mm	16.0 mm	0.8 mm
Substrate			NA	NA	NA	(Particle board) -44.0 mm
Reaction to fire	4.2.2	EN 13823 EN 13501-1	B-s1, d0	B-s1, d0	C-s1, d2	C-s1, d0
Fire resistance	4.3.2	EN 13501-2	NPD	NPD	NPD	NPD
Water vapour permeability	4.4	EN ISO 12572	NPD	NPD	NPD	NPD
Resistance to fixings	4.5	ISO 13894-1	≥ 2000	≥4000	≥ 4000	No Requirement
Direct airborne sound insulation	4.6	EN ISO 140-3 EN ISO 717-1	NPD	NPD	NPD	NPD
Bonding strength N/mm <sup>2</sup>	4.7	EN ISO 13894-1	1,49	1,42	1,42	NPD
Flexural strength N/mm <sup>2</sup>	4.8	EN ISO 178	≥ 80	≥ 80	≥ 80	NPD
Flexural Modulus N/mm <sup>2</sup>		EN ISO 178	≥ 9000	≥ 9000	≥ 9000	
Tensile Strength N/mm <sup>2</sup>		ISO 527-2	84,3	77,1	77,1	
Thermal resistance/ Conductivity W/mo K	4.9	EN 12524 EN 12664	0,24	0,24	0,24	NPD
Content of pentachlorophenol	4.10.1	EN 323	NPD	NPD	NPD	NPD
Release of formaldehyde (µg/m <sup>3</sup> )	4.11.1	EN 717-1 UL-2818	9 (7.3 ppb)	9 (7.3 ppb)	9 (7.3 ppb)	HPL- 9 (7.3 ppb), SUBSTRATE EN13986 - E1
Sound absorption	4.11.2	EN ISO 354 EN ISO 11654	NPD	NPD	NPD	NPD
Thermal shock resistance	4.12.1	EN 438-2	pass	pass	pass	NPD
Durability	4.13	ISO 13894-1	Resistance to wet conditions pass	Immersion in boiling water pass	Immersion in boiling water pass	NPD
		EN ISO 1183-1, Density-g/cm <sup>3</sup>	≥ 1.350	≥ 1.400	≥ 1.400	Particle board - 0.620, HPL- 1.380, Composite Panel -0.654
		EN 438-2	Rating - 5, Mass Increase Max 2.5 %	NPD	NPD	NPD



Manager:

*Anna Vasileva*



dipl. eng. Anna Vasileva

Issued:  
Burgas, 09 August 2023

Ref. No. 03-00

## ANNEX II TO CERTIFICATE OF CONSTANCY OF PERFORMANCE 1922 - CPR - 0751/09.08.2023

List of controlled characteristics:

Characteristics, dimension	Clause	Method	Results			
			COMPACTBRANDS			
			Greenlam New Mika FR (EDF)	Greenlam New Mika FR (CGF)	Greenlam New Mika FR (CGF)	Greenlam New Mika FR (CGF)
Thickness			8.0 mm	3.0 mm	6.0 mm	8.0 mm
Substrate			NA	NA	NA	NA
Reaction to fire	4.2.2	EN 13823 EN 13501-1	B-s1, d0	B-s1, d0	B-s1, d0	B-s1, d0
Fire resistance	4.3.2	EN 13501-2	NPD	NPD	NPD	NPD
Water vapour permeability	4.4	EN ISO 12572	NPD	NPD	NPD	NPD
Resistance to fixings	4.5	ISO 13894-1	> 3000	> 1000	> 2000	> 3000
Direct airborne sound insulation	4.6	EN ISO 140-3 EN ISO 717-1	NPD	NPD	NPD	NPD
Bonding strength N/mm <sup>2</sup>	4.7	EN ISO 13894-1	-	-	-	-
Flexural strength N/mm <sup>2</sup>	4.8	EN ISO 178	≥ 80	≥ 80	≥ 80	≥ 80
Flexural Modulus N/mm <sup>2</sup>		EN ISO 178	≥ 9000	≥ 9000	≥ 9000	≥ 9000
Tensile Strength N/mm <sup>2</sup>		ISO 527-2	84,3	84,3	84,3	84,3
Thermal resistance/ Conductivity W/m <sup>o</sup> K	4.9	EN 12524 EN 12664	0,24	0,24	0,24	0,24
Content of pentachlorophenol	4.10.1	EN 323	NPD	NPD	NPD	NPD
Release of formaldehyde (µg/m <sup>3</sup> )	4.11.1	EN 717-1 UL- 2818	9 (7.3 ppb)	9 (7.3 ppb)	9 (7.3 ppb)	9 (7.3 ppb)
Sound absorption	4.11.2	EN ISO 354 EN ISO 11654	NPD	NPD	NPD	NPD
Thermal shock resistance	4.12.1	EN 438-2	pass	pass	pass	pass
Durability	4.13	ISO 13894-1	Resistance to wet conditions pass	Immersion in boiling water pass	Immersion in boiling water pass	Immersion in boiling water pass
		EN ISO 1183-1, Density-g/cm <sup>3</sup>	≥ 1.350	≥ 1350	≥ 1.350	≥ 1.350
		EN 438-2	Rating - 5, Mass Increase Max 2.5 %	NPD	NPD	NPD



Manager: *Anna Vasileva*

Dedal dipl. eng. Anna Vasileva

Issued:  
Burgas, 09 August 2023

Ref. No. 03-00